



INSTALLATION INSTRUCTIONS

Accessory

HITCH BALL
P/N 0SL68-HL5-A10

Application

SXS520/520M2

Publications No.

MII 55186

Issue Date

July 2024

Honda Dealer: Please give a copy of these instructions to your customer.

PARTS LIST

No.	Description	Qty
(1)	Hitch ball	1
(2)	Washer	1
(3)	Nut	1

USE AND CARE INFORMATION

- Never exceed the maximum tow weight or tongue weight of your vehicle. Refer to the Owner's Manual for additional information on towing a trailer.
- Mounting hole must not exceed shank diameter more than .060 inch (1/16 inch).
- Always include a lock washer to install the hitch ball.
- Ball shank must extend at least one thread beyond nut.
- Use only with couplers marked with 1-7/8" hitch ball size.
- Do not fasten safety chain to hitch ball.
ABSOLUTELY do not attach tow chain, cable, rope, elastic strap, or elastic rope to hitch ball.
- Check the hitch ball tightness before each use.
- Place a small amount of heavy oil or grease on ball before each use.
- Do not allow oil or grease to accumulate under the flange or on the nut and threads.
- Always use a Honda Draw Bar (P/N 0SL68-HL5-A00) with this accessory.

TOOLS AND SUPPLIES REQUIRED

- 1 1/8 inch wrench
- 1 5/8 inch wrench

INSTALLATION

1. Install the hitch ball shank into the draw bar.
2. Place the washer between the draw bar and the nut.
3. Torque the nut to 160 ft*lb.

